

Notice Inviting e-Tender

West Bengal Medical Services Corporation Limited Swasthya Sathi GN-29, Salt Lake, Sector-V Kolkata-700091

Phone No (033) 40340307/20

E mail: procurement@wbmsc.gov.in

Supply and Commissioning of different types of Medical Equipment at Medical College and Hospital of the Govt. of West Bengal

(Submission of Bid through *online*)

Bid Reference No.: WBMSCL/NIT-215/2018 Dated-12.10.2018

Amendment-II

REVISED TECHNICAL SPECIFICATION

PCR MACHINE

1. THERMAL CYCLER FOR PCR OPEN SYSTEM		
PERFORMANCE / FEATURE	THRESHOLD LIMIT/ RANGE	
TEMPERATURE RANGE (°C)	(0 -90) OR MORE	
NUMBER OF THERMAL WELLS	32 OR MORE	
SELECTABLE HEATING LID TEMPERATURE (°C)	100 OR MORE	
REACTION VOLUME(µL)	(10-30) OR MORE	
TEMPERATURE ACCURACY (°C)	WITHIN± 0.25	
TEMPERATURE UNIFORMITY BETWEEN	WITHIN± 0.5	
SAMPLES (°C)		
COMPATIBILITY WITH AMBIENT	(10 to 35) OR MORE	
TEMPERATURE IN °C		
MUST HAVE SPECIFICATIONS		
PERFORMANCE / FEATURE	YES / NO	
CONSUMABLES ARE NOT COMPANY OR		
BRAND SPECIFIC		
AUTOMATIC PROGRAMABLE RUN		
LOW - HIGH THROUGHPUT CAPABILITIES FOR		

ALL PCR AMPLIFICATION NEEDS		
GRADIENT SYSTEM / VERIFLEX		
END PROGRAMME COOLING BELOW		
AMBIENT TEMPERATURE		
AUTO RESTART FACILITY		
2 or more STEP PROGRAMME TEMPLATES		
DISPLAY WITH GRAPHICAL REPRESENTATION		
PROGRAMME NAMING		
PASSWORD PROTECTION		
PROGRAMME STORAGE CAPACITY		
PAUSE BUTTON		
STOP BUTTON		
ACCOMMODATE 2 OR MORE BLOCKS AT A		
TIME		
END PROGRAMME ALARM		
2. MOLECULAR IMAGER O	EL DOC	
PARAMETER / FEATURE	THRESHOLD LIMIT/RANGE	
OPERATING TEMPERATURE (° C)	(10 to 35) OR MORE	
MUST HAVE FEATURES		
PARAMETER / FEATURE	YES /NO	
EXCITATION SOURCE - TRANS UV AND TRANS		
WHITE		
UV / BLUE CONVERSION SCREEN		
ILLUMINATION CONTROL – 2 OR MORE		
SOURCE TRANS UV, TRANS WHITE, EPI- WHITE		
(IN CASE MORE THAN 2 IS SUPPLIED)		
COMPATIBILITY WITH FOLLOWING DYES -		
QDOTR, SYBR SAFER, ETHIDIUM BROMIDE		
COMPATIBLE WITH BOTH PRE CAST GEL AND		
POUR IT YOURSELF GEL (AGAROSE OR		
POLYACRAMIDE)		
COMPATIBLE WITH DENSITOMETRY		
SHOULD PERFORM REAL TIME SAMPLE		
IMAGING		
IMAGE LAB SOFTWARE INTERFACED WITH		
TABLE TOP COMPUTER/ LAPTOP 3. HORIZONTAL ELECTROPHORESIS	MAACHINIE EOD DCD	
PERFORMANCE / FEATURE	THRESHOLD LIMIT/RANGE	
GEL SIZE (CM)	10 X 8	
SPACERS THICKNESS in MM,	0.75 to 1.0 OR MORE	
RIDGED COMBS (WELLS)	10 to 15 OR MORE	
	TO TO TO OK WORL	
number of <mark>wells</mark> can be run		
SIMULTANEOUSLY	8 OR MORE	

POWER PACK VOLTAGE	5 - 200 OR MORE
POWER PACK VOLTAGE INCREMENT STEP	1
POWER PACK POWER IN WATT	200 OR MORE
OUTPUT TERMINAL (in Number)	2 OR MORE
MUST HAVE SPECIFICATION	TIONS
PERFORMANCE / FEATURE	YES / NO
CONSTANT VOLTAGE AND CURRENT IN	
POWER PACK	
SPACERS WITH GLASS PLATE	
CAPABLE OF DNA ELECTROPHORESIS	
BUFFER TANK WITH PLATINUM ELECTRODES	
SAFETY FEATURES:	
LOAD DETECTION,	
GROUND LEAK DETECTION,	
SUDDEN LOAD CHANGE DETECTION,	
OVERLOAD / SHORT CIRCUITS DETECTION,	
AUTO POWER UP AFTER POWER	
UV TRANSPARENT GELL TRAYS, COMBS	
ONLINE UPS OF APPROPRIATE CAPACITY FOR	
THERMAL CYCLER FOR PCR OPEN SYSTEM,	
MOLECULAR IMAGER GEL DOC AND	
HORIZONTAL ELECTROPHORESIS MACHINE	
FOR PCR	
QUALITY STANDARD AND SAFETY CERTIFIC	CATION FOR ALL 3 UNITS
EUROPEAN CE OR US FDA	