

West Bengal Medical Services Corporation Limited Swasthya Sathi GN-29, Salt Lake, Sector-V Kolkata-700091

Phone No (033) 40340308/319 E mail: <u>procurement@wbmsc.gov.in</u>

Supply and Commissioning of Medical equipment at Paediatric wards for Clinical management of Children suffering from MIS-C

2nd call of the bid reference no. WBMSCL/NIT-57/2022 (Schedule-I), Dated- 21.02.2022

Bid Reference No: WBMSCL/NIT-107/2022

Dated -23.03.2022

The following amendments has been made in the tender document, <u>Amendment – I</u>

<u>Schedule – II</u> Cerebral and Somatic Oximeter, rSO2 range 15 to 95

<u>Generic</u>

Use:-It may be used for cerebral oximetry, somatic oximetry or both simultaneously. Number of channels:-4

Application:-The Cerebral/Somatic Oximeter monitor is a noninvasive oximeter which simultaneously monitors changes in regional blood oxygen saturation in the brain and skeletal muscle tissue of the body.

Dimension of the monitor

Depth:-7.5 inch Height:-9.5 inch Width:-11.25 inch

Technical Parameter

Mode Specific Event Marking List Should have published emitter-sensor spacing validation Reading accuracy during non - normocapnic conditions Sensor Type: - Adult, Pediatric, Neonates. Sensor Quantity (Adult, Pediatric, Neonates):- 50 nos. for each type to be supplied with the machine. Electrical Requirement: -100-240 VAC & Frequency oh 50/60 HZ Alarm: - audible, visible **R SO2 range:-**15-95 Signal strength indicator has in this parameter for each channel or sensor to better reflect interference Preamplifier cable length: - 4.5 meter Should have at least 500 or more published / peer reviewed articles Software for Data Analysis: - INVOS Analytical Tool Data Storage & Transfer: - USB Port Should have basic line setting option Should have options to change Time Scale of graph with Minimum 1 hour to Maximum 24 hours Should have at least two clinical study with improved patient outcome Minimum Weight for patient: -2.58 kg and above Defined rSO2 measurements sites: - Forehead, Renal Area, Abdomen, Chest, Forearm, Upper Arm, Calf, Upper Leg. Data Storage: - up to 24 hours of data per case file Patient Range: - Adult, Pediatric, Neonates. Modes to be selected at a time: -OR, ICU, Vascular, NICU Soma sensor cable: -1.5 meter Battery backup: -20 minute Sensors has25mm separations between source to detector to get reliable detection of substantial absorption signal.

Test Report

Address of the Lab: -Munich, Germany Test Report Number: -75939661 Test Report Date: -16/1/2019 Name of the Lab: - TUV SUD Product Service GmBH Availability of Type Test Report for conformity of:-USFDA Parameters from any ILAC/NABL accredited/Central Gov.LAB

<u>Test Reports</u> Test report to be submitted to the Buyer on Demand

<u>Certification</u> :- EUROPEAN CE (4 digits) or US FDA approved product.